



CAB 800X1000 BL

19" Floor-standing Cabinet, 800x1000mm, black RAL9005

Features

- Safety-glass door
- 2 depth-adjustable 19-inch mounting levels
- Material: 1.5mm steel
- Roof panel with 3 cable entries and openings for fan unit
- Removable side panels with locking option
- Removable rear panel with locking option
- Height-adjustable leveling feet
- Door with swing-handle lock and single-point locking
- Surface (doors, side panels, base and roof cover):
 - Antistatic powder coating
 - Galvanized 19" rails
- RoHS compliant, UL and Gost-R certified
- The network/server cabinet is supplied fully assembled
- Additional models available on request



Description

Wirewin® steel network cabinets offer an excellent price/performance ratio and are suitable for high-density applications as well as data center applications. Their modular design makes them a sound investment for the future. The cabinets offer various options for routing copper and fiber optic cabling and enable easy installation while still providing maximum capacity for high-density applications! Rear and side panels are easy to remove, cable entry is possible through 3 openings, depth-adjustable profile rails (2 mounting levels).



CAB 800X1000 BL

19" Floor-standing Cabinet, 800x1000mm, black RAL9005

Technical Data

Parameter	Value
Number of rack units (U)	42 / 47
Number of doors	1
Type of ventilation	none
Design	with fixed frame
Surface finish	powder-coated
Profile rail design	L-shaped
Design	Floor-standing cabinet
Width	800 mm
External width	800 mm
Internal width	703 mm
Color	Black
Height	2033 mm / 2255 mm
External height	2033 mm / 2255 mm
Internal height	1873 mm / 2095 mm
Material	1.5 mm steel
Front door material	Glass
Rear door material	Steel
Max. load capacity	2000 kg
With roof panel	Yes
With grounding	Yes
With front door	Yes



CAB 800X1000 BL

19" Floor-standing Cabinet, 800x1000mm, black RAL9005

Technical Data

Parameter	Value
With rear door	Yes
With side panels	Yes
With viewing door	Yes
With plinth	No
With vertical cable management	No
Mounting level	front and rear
Mounting depth of 19-inch rails	123 - 773 mm
Product family	Floor-standing cabinet Pro
RAL number	RAL9005
Mounting grid	482,6 mm (19 inch)
Degree of protection (IP)	IP20
Depth	1000 mm
External depth	1000 mm
Internal depth	950 mm
Front door locking	Single-point
Rear door locking	Single-point
Material	Steel
Dismantlable	Yes
Certificates / Approvals	RoHS, UL and Gost-R certified