

CAT6 SURFACE OUTLET, SHIELDED, RAL9010, LSA CONNECTOR

DD-TRIO-C6 AP2 WS

DESCRIPTION

CAT6 shielded outlet with LSA socket. This outlet allows data transmission for up to 1 Gigabit Ethernet. The front plate has 2 dust-protected, shielded RJ45 ports. The cables can be connected from the left and right.

ISO / IEC 11801, EN 50173-1 Class E up to 250MHz
Suitable for Power-over-Ethernet applications
Service life:> 750 mating cycles

FEATURES

- CAT 6 ISO/IEC 11801, EN50173
- Size: 80 x 80 x 381mm
- Color: White / Ivory
- Suitable for 1 Gbit Ethernet
- Integrated strain relief for installation
- 2 x shielded RJ45 sockets
- Backbox available
- Trunking system, surface/flush mount ready
- Made of zinc alloy conform to the industry standard of shielding effect
- Compact outlet, easy to install
- Compact outlet, has embedded icons and label positions for easy identification
- Central plate with integrated dust covers

CONSTRUCTION

Description	Parameter
Contact resistance(max)	20mΩ
Insulation resistance(min)	500MΩ
Return loss(dB)	6.3dB
EAN number	9120072487187
Packaging	single packed
Weight	0,3 kg
PARTNUMBER	
DD-TRIO-C6 AP2 WS	



CAT6 SURFACE OUTLET, SHIELDED, RAL9010, LSA CONNECTOR

DD-TRIO-C6 AP2 WS

PRODUCT DIMENSION

