



Note:
RoHS 2.0 & Reach Compliant

Test Grade Designation:Each to Reference		
Grade	IL/RL	Standard
Insertion Loss (IL)	≤0.2dB	IEC 61300-3-4
Return Loss (RL)	APC≥60dB, UPC≥50dB	IEC 61300-3-6
Test Wavelength	1310nm	
End face inspection	×400	

ITEM NO.	Length
LSP-09 SC-SC 1.0	1m
LSP-09 SC-SC 10.0	10m
LSP-09 SC-SC 2.0	2m
LSP-09 SC-SC 3.0	3m
LSP-09 SC-SC 5.0	5m

Packing:1pc/PE Bag+Lightwin Label

MATERIAL LIST:

⑦	SC 3.0 Boot Black	1 pc	
⑥	SC UPC Connector Blue	1 pc	
⑤	SC Dust Cap Black	1 pc	
④	Fiber Optical Cable Yellow G652.D OS2 9/125um Simplex Ø3.0±0.2 LSZH	L	
③	SC 3.0 Boot Black	1 pc	
②	SC UPC Connector Blue	1 pc	
①	SC Dust Cap Black	1 pc	
NO.	SPECIFICATION STANDARD	QT' Y	REMARK

BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

Lightwin®
European Fibre Optic Solutions

CUSTOMER		ITEM NO.	See the chart	
PRODUCT NAME	SC/UPC-SC/UPC Simplex OS2 Patch Cord Yellow 3.0		UNIT	MM
DRAWNBY	CHECKBY	APPOBY	DATE	
TT	LF		2021-06-08	