



LWC-10/100-SF-S20-B

WDM Converter 100Base-LX, Singlemode, 20KM

Features

- Fast Ethernet transmission over a single fiber
- Dedicated chipset
- Long-life laser
- External power supply included
- Compatible with Lightwin chassis
- Transmission: Singlemode
- Data rate: 100 Mb/s
- Wavelength: 1550 nm
- Distance: 20 km
- Connections: 1x Simplex SC, 1x RJ45
- Mode: Single fiber, WDM



Description

Lightwin high-quality singlemode WDM media converters offer important advantages compared with alternative no-name converters. All Lightwin converters support 10/100Base-T auto-negotiation and Auto-MDI/MDI-X. Lightwin converters provide a significantly longer service life thanks to the specially selected laser. All Lightwin converters are supplied with an external power supply and can be used with the optional Lightwin chassis.



LWC-10/100-SF-S20-B

WDM Converter 100Base-LX, Singlemode, 20KM

Technical Data

Parameter	Value
Connection	Simplex SC
Fiber optic ports	1x Simplex SC
Copper ports	1x RJ45
Data rate	100 Mb/s
Distance	20 km
Managed/Unmanaged	Unmanaged
TX wavelength	1550 nm
Transmission	Singlemode
EAN Number	9120046984155
Weight	0.4 kg